

## Nittocon B material(Barium Titanate) Low-Profile Spec.

形 式 名 Part No.	端子 構造 Term.	公 称 静電容量 PF±50%	直 流 定 格 電 圧 KV	寸 法 (mm)			備 考
				Dφ ±10%	T ±3	H ±3	
BE-60S	S	20000	4.0	60	4~1	23~20	
BE-60S	S	10000	5.0	60	8~4	27~23	
BE-60S	S	5000	6.0	60	9~5	28~24	
BE-50S	S	15000	2.5	50	4~1	23~20	
BE-50S	S	8000	3.0	50	6~2	25~21	
BE-50S	S	5000	4.0	50	7~2	26~21	
BE-50S	S	3000	5.0	50	7~3	26~22	
BE-50S	S	2000	5.0	50	7~3	26~22	
BE-40S	S	10000	2.5	40	4~1	23~20	
BE-40S	S	5000	3.0	40	5~1	24~20	
BE-40S	S	3000	4.0	40	5~1	24~20	
BE-40S	S	2000	4.0	40	6~2	25~21	
BE-40S	S	1000	4.0	40	6~2	25~21	
BE-30S	S	10000	1.0	30	3~0.5	22~19	
BE-30S	S	5000	2.0	30	4~1	23~20	
BE-30S	S	3000	3.0	30	5~1	24~20	
BE-30S	S	2000	3.0	30	5~1	24~20	
BE-30S	S	1000	3.0	30	5~1	24~20	
BE-20S	S	2000	2.0	20	5~1	20~16	
BE-20S	S	1000	2.0	20	4~1	19~16	

※RoHS対応品に関しては別途ご相談ください。

\* **Please ask “RoHS” compliance if needed.**

**TRY-ALL**  
www.try-all-jpn.com